



Crosses & Tees List

**Additional sizes available (call for details)*

AAI Code	SIZE AND DESCRIPTION OF CROSS AND TEE	API DESIGNATION
CRS-21/21-5	2 1/16" 5,000 psi x 2 1/16" 5,000 psi x 2 1/16" 5,000 psi x 2 1/16" 5,000 psi, studded	PR-1, PSL-2; L-U
CRS-21/21-10	2 1/16" 10,000 psi x 2 1/16" 10,000 psi x 2 1/16" 10,000 psi x 2 1/16" 10,000 psi, studded	PR-1, PSL-3; L-U
CRS-21/21-15	2 1/16" 15,000 psi x 2 1/16" 15,000 psi x 2 1/16" 15,000 psi x 2 1/16" 15,000 psi, studded	PR-1, PSL-3; L-U
CRS-31/31-5	3 1/8" 5,000 psi x 3 1/8" 5,000 psi x 3 1/8" 5,000 psi x 3 1/8" 5,000 psi, studded	PR-1, PSL-2; L-U
CRS-31/31-10	3 1/16" 10,000 psi x 3 1/16" 10,000 psi x 3 1/16" 10,000 psi x 3 1/16" 10,000 psi, studded	PR-1, PSL-3; L-U
CRS-41/21-5	4 1/16" 5,000 psi x 2 1/16" 5,000 psi x 4 1/16" 5,000 psi x 2 1/16" 5,000 psi, studded	PR-1, PSL-2; L-U
CRS-41/21-15	4 1/16" 15,000 psi x 2 1/16" 15,000 psi x 4 1/16" 15,000 psi x 2 1/16" 15,000 psi, studded	PR-1, PSL-3; L-U
CRS-41/41-15	4 1/16" 15,000 psi x 4 1/16" 15,000 psi x 4 1/16" 15,000 psi x 4 1/16" 15,000 psi, studded	PR-1, PSL-3; L-U
CRS-71/21-5	7 1/16" 5,000 psi x 2 1/16" 5,000 psi x 7 1/16" 5,000 psi x 2 1/16" 5,000 psi, studded	PR-1, PSL-2; L-U
CRS-71/41-5	7 1/16" 5,000 psi x 4 1/16" 5,000 psi x 7 1/16" 5,000 psi x 4 1/16" 5,000 psi studded by studded	PR-1, PSL-2; L-U
CRS-71/41-10	7 1/16" 10,000 psi x 4 1/16" 10,000 psi x 7 1/16" 10,000 psi x 4 1/16" 10,000 psi, studded	PR-1, PSL-3; L-U
TE-29-5	2 9/16" 5,000 psi x 2 9/16" 5,000 psi x 2 9/16" 5,000 psi, studded	PR-1, PSL-2; L-U
TE-29/113-10	2 9/16" 10,000 psi x 1 13/16" 10,000 psi x 2 9/16" 10,000 psi, studded	PR-1, PSL-3; L-U
TE-29-15	2 9/16" 15,000 psi x 2 9/16" 15,000 psi x 2 9/16" 15,000 psi, studded	PR-1, PSL-3; L-U
TE-21-5	2 1/16" 5,000 psi x 2 1/16" 5,000 psi, x 2 1/16" 5,000 psi, studded	PR-1, PSL-2; L-U
TE-21-10	2 1/16" 10,000 psi x 2 1/16" 10,000 psi x 2 1/16" 10,000 psi, studded	PR-1, PSL-3; L-U
TE-21-15	2 1/16" 15,000 psi x 2 1/16" 15,000 psi x 2 1/16" 15,000 psi, studded	PR-1, PSL-3; L-U
TE-31-5	3 1/8" 5,000 psi x 3 1/8" 5,000 psi x 3 1/8" 5,000 psi, studded	PR-1, PSL-2; L-U